



SPECIFICATION

Model NO.	LIN60S100	LIN60S130	LIN60S130	LIN60SE200	LIN60S200	LIN60SV200	LIN60SL200	LIN604XSL200	LIN60A200	LIN60XA200	LIN60S300	LIN60A300	LIN60S400	LIN604XS400	LIN60A400	LIN60S500
Camera																
Image Sensor	OV9732	S3130	IMX225	IMX323	IMX323	OV2718	IMX290	IMX290	IMX322	IMX322	IMX124	IMX124	OV4689	OV4689	OV4689	IMX178
Main processor	Hi3518EV200	Hi3518EV200	Hi3518EV200	Hi3518EV200	Hi3516CV200	Hi3516CV200	Hi3516D	Hi3516D	S2L33	S2L33	Hi3516D	S2L55	Hi3516D	Hi3516D	S2L55	Hi3516A
Resolution	720P	960P	960P	1080P	1080P	1080P	1080P	1080P	1080P	1080P	3MP	3MP	4MP	4MP	4MP	5MP
Effective Pixels	1280(H)*720(V)	1280(H)*960(V)	1305(H)*977(V)	1920(H)*1080(V)	1985(H)*1105(V)	1920(H)*1080(V)	1945(H)*1097(V)	1945(H)*1097(V)	1984(H)*1225(V)	1984(H)*1225(V)	2065(H)*1553(V)	2065(H)*1553(V)	2688(H)*1520(V)	2688(H)*1520(V)	2688(H)*1520(V)	2592(H)*1944(V)
Compression	H.264/JPEG/AVI	H.264/JPEG/AVI	H.264/JPEG/AVI	H.264/JPEG/AVI	H.264/JPEG/AVI	H.264/JPEG/AVI	H.264/H.265/JPEG/AVI	H.264/H.265/JPEG/AVI	H.264/JPEG/AVI	H.264/JPEG/AVI	H.264/H.265/JPEG/AVI	H.264/JPEG/AVI	H.264/H.265/JPEG/AVI	H.264/H.265/JPEG/AVI	H.264/JPEG/AVI	H.264/H.265/JPEG/AVI
TV System	PAL/NTSC															
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec															
S/N Ratio	≥52dB															
Scanning System	Progressive															
Video Output	Network															
Lens																
Focus Length	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	3.6mm
Focus Control	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Auto	Manual	Auto	Manual	Manual	Manual	Auto	Manual	Fixed
Lens Type	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Auto	Manual	Auto	Manual	Manual	Manual	Auto	Manual	Fixed
Pixels	2M Pixels	2M Pixels	2M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	5M Pixels	5M Pixels	5M Pixels	5M Pixels	5M Pixels	6M Pixels
Night Vision																
Infrared LED	42μ x 4PCS															
Infrared Distance	60M															
IR Status	Under 10 Lux By CDS															
IR Power On	CDS Auto Control															
Network																
Ethernet	RJ-45 (10/100Base-T)															
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP															
ONVIF	Support ONVIF 2.4															
P2P	YES, Support QR Code															
POE	Optional, Support IEEE 802.3af															
WIFI	N/A															
Video Delay	0.3S (Within the Lan)															
Main Stream 1	1280*720@25fps	1280*960@25fps	1280*960@25fps	1920*1080@15fps	1920*1080@25fps	1920*1080@25fps	1920*1080@30fps	1920*1080@30fps	1920*1080@30fps	1920*1080@30fps	2048*1536@30fps	2048*1536@30fps	2560*1440@20fps	2560*1440@20fps	2560*1520@20fps	2592*1944@30fps
Main Stream 2	/	1280*720@25fps	/	/	/	/	/	/	/	/	1920*1080@30fps	1920*1080@30fps	2304*1296@30fps	2304*1296@30fps	2048*1520@20fps	2048*1520@30fps
Main Stream 3	/	/	/	/	/	/	/	/	/	/	/	/	1920*1080@30fps	1920*1080@30fps	1920*1080@20fps	1080@30fps
Sub Stream 1	720*480@25fps	720*480@25fps	720*480@25fps	720*480@15fps	720*480@25fps	720*480@25fps	720*480@30fps	720*480@30fps	720*576@30fps	720*576@30fps	720*480@30fps	720*480@30fps	720*480@20fps 720*480@30fps	720*480@20fps 720*480@30fps	720*480@20fps	720*480@30fps
Sub Stream 2	/	/	/	/	/	/	/	/	720*480@30fps	720*480@30fps	/	640*360@30fps	/	/	640*360@20fps	/
Sub Stream 3	/	/	/	/	/	/	/	/	640*360@30fps	640*360@30fps	/	/	/	/	/	/
Tri Stream	352*288@25fps	/	/	352*288@15fps	352*288@25fps	352*288@25fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@20fps 352*288@30fps	352*288@20fps 352*288@30fps	352*288@20fps	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari															
Smart Phone	iPhone, iPad, Android, Android Pad															
Camera Features																
Day/Night	Color/ B&W (IR-CUT)															
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)															
Corridor Pattern	/	/	/	/	/	/	Support	Support	/	/	Support	/	Support	Support	/	Support
Defog Mode	Support	Support	Support	Support	Support	Support	Support	Support	/	/	Support	/	Support	Support	/	Support
ROI	Support	Support	Support	Support	Support	Support	Support	Support	/	/	Support	/	Support	Support	/	Support
Motion Detection	Support															
Privacy Masking	3 Rectangular Zone															
WDR	Support															
Recording Mode	NVR/NAS/CMS/Web															
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands															
General																
Housing	Metal , IP66															
Anti-cut Bracket	YES															
IR Cut Filter	YES															
Operation Temperature	-20℃ ~ +60℃ RH95% Max															
Storage Temperature	-20℃ ~ +60℃ RH95% Max															
Power Source	DC12V±10%, 1000mA															
Dimension	275(W) x 91(H) x 80(D)mm															
Weight	1.4Kg															